







The Strongest Connection


Normal Gauge	&	Heavy Gauge
DESCRIPTION	CODE	SIZE
	n12	1/2"
	n34	3/4"
	n1	1"
	n114	1 1/4"
	n112	1 1/2"
	n2	2"


Reduction Insert	DESCRIPTION	SIZE
	ri3412	3/4" x 1/2"
	ri134	1" x 3/4"
	ri112	1" x 1/2"

IBC TANK CONNECTOR various	DESCRIPTION	SIZE
	IBCBT12	with 1/2" tap
	IBC12G	with 1/2" joiner
	IBC	BSP 1" & 3/4" BSP F
	IBCMOL	with Molasses spout
	IBC34G	with 3/4" joiner
	IBCBLANK	with Blank


Pipe Cutters	DESCRIPTION	SIZE
	pc1	42mm max


Blank Insert: use to blank off one end of Gripmax fittings
Can be drilled out to use a connection when required.

	IB12	1/2"
	IB34	3/4"


3/4" spray gun	DESCRIPTION	SIZE
	RAY1	3/4" spray gun






Normal Gauge	&	Heavy Gauge
DESCRIPTION	CODE	SIZE
	TFV	1/2"-3/4"-1"

Ball/ Float 6"	DESCRIPTION	SIZE
	FVBALL	6" diameter

Threaded Pipe	DESCRIPTION	SIZE
	complete with female connector	
	tb12	1/2" x 150mm
	tb34	3/4" x 150mm
	tb1	1" x 150mm

Mini Fill Valve for small drinkers	DESCRIPTION	SIZE
	MFV12	1/2"

NG & HG Insert	DESCRIPTION	SIZE
	i12	1/2"
	i34	3/4"
	i1	1"
	i114	1 1/4"
	i112	1 1/2"

COLLET	DESCRIPTION	SIZE
	normal	
	nc12	1/2"
	nc34	3/4"
	nc1	1"
	nc114	1 1/4"
	nc112	1 1/2"
	heavy	
	hc12	1/2"
	hc34	3/4"
	hc1	1"
	hc114	1 1/4"
hc112	1 1/2"	



Use Gripmax pipes with Gripmax fittings for manufacturer's warranty